The Reliable Supplier for Power System Solution



NW-B Series
Powered by Baudoin Engines

NWB / 357

Ratings

Output Ratings	Prime Power	Standby Power
	323 kVA / 258,4 kW	357 kVA / 285,6 kW

Variable genset continuous power (PRP - Prime Power) : The assessment criterion for the variable prime power is the permissible average power output over 24 hours. The permissible average power output must not exceed a percentage of the variable genset continuous power output specified by the manufacturer of the genset. The values are between 40 % and 80 %, depending on the system. The operating time of the genset is not limited. The typical area of application for this is gensets that supply systems continuously in stand-alone operation.

Limited-time running power Maximum power (LTP - Limited-Time Running Power) is the maximum power that a genset can deliver within 500 hours per year. The genset may be operated continuously for 300 hours.

Performance Data

Engine Brand & Model		Baudouin / 6M16G350/5
Alternator Brand & Model		Newpower / NW/N357
Frequency & Phase		50 Hz & 3 Phase
Engine Speed (RPM)		1500
Tank Capacity (L)		385
Fuel Consumption (L/h)	110% Load	78,4
	100% Load	70,5
	75% Load	52,3
	50% Load	35,4
Standard Noise Level @ 7m (Soundproof Sets)		ca. 72 dB

Dimensions and Weights

Content		Open Skid	Canopied
Dimensions (mm)	L	3000 mm	3940 mm
	B	1300 mm	1300 mm
	H	1600 mm	1850 mm
Weights (Kg)		2459 kg	3024 kg

The dimensions of the unit may vary depending on the equipment. Please inform us exactly about the area of application.

The Reliable Supplier for Power System Solution

Engine Features

Baudouin is a company founded in France in 1918 that manufactures diesel engines primarily for marine applications and generators. Baudouin's generator engines are known for their high performance, reliability and durability. These engines are available in various power ranges and are often used in industrial plants, ships, harbors, emergency power supplies and other applications. Thanks to their high efficiency, strong performance, long service life and environmentally friendly characteristics, Baudouin motors have become a popular choice in industrial and marine applications.

Typical Engine Data / Engine Brand & Model: Baudouin / 6M16G350/5

No. Of Cylinders / Alignment	6 / Inline	Displacement (L)	9,726
Bore / Stroke	126 mm / 130 mm		
Induction	Turbocharge-Aftercooler	Governing Type	Electronic
Cooling Method	Water	Net Weight (kg)	1021
Lubricant Oil	15W-40	Exhaust Outlet Temperature 50 Hz	550
Emission Standard	Stage II	Exhaust Gas Flow 50 Hz	58,2
Oil Capacity (L)	26	Combustion Air Flow 50 Hz	20,8
Engine Gross Power (Standby 50 Hz)	320 kW	Cooling Air Flow 50 Hz	450
Compression Ratio	17:1	Coolant Capacity (L)	50

Alternator Data / Brand & Model: Newpower & NWN 357

Nominal Performance	323 kVA	Insulation class	H
Maximum Performance	357 kVA	Protection	IP23
Winding	%100 Copper	Winding pitch	2 / 3
Brush type	Brushless	Amortisseur winding	Full
Generator type	Synchronise	Ambient temp	50 ºC
Bearing	single	Stator rated temp	125 ºC
A.V.R.	SX440 / SX460	Phase Sequence	A(U), B(V), C(W)
Voltage Regulation	±1.0%	THF(BS EN60034-1)	<2%
Trigger system	Self Excitation	TIF(NEMA MG 1-22)	<50

Controlsystem:



InteliLite 4 AMF 8 is a single genset controller for standby and prime power applications. Intuitive, flexible, easy to install and use, the InteliLite 4 AMF 8 controller offers multiple configuration options to create the best solution for on-site and remote control and monitoring of your gensets.

The Reliable Supplier for Power System Solution

Characteristic

Included	Optional
o 4-stroke 1500 rpm, water-cooled heavy-duty diesel engine o Replaceable dry type air filter o Heat resistant cooler for 50°C. o Flexible oil lines and oil drain valve o Single layer, brushless AC generator o batteries and cables o Circuit breaker - RCD protection o Industrial silencer Soundproof Plus o battery charger o cooling water heater o sockets o Galvanized canopy o circuit diagram o User Manual and Instruction Manual	o Automatic transfer switch o External fuel tank o fuel heater o Oil heater o Fuel filling system (automatic / manual) o Analog displays

NEWPOWER

167/5000

We reserve the right to make changes to the model, specifications, color, configuration and accessories without prior notice.Please contact us before placing your order.