The Reliable Supplier for Power System Solution



NW-B Series
Powered by Baudoin Engines

NWB / 138

Ratings

Output Ratings	Prime Power	Standby Power
	125 kVA / 100 kW	138 kVA / 110 kW

Variable genset continuous power (PRP - Prime Power) : The assessment criterion for the variable prime power is the permissible average power output over 24 hours. The permissible average power output must not exceed a percentage of the variable genset continuous power output specified by the manufacturer of the genset. The values are between 40 % and 80 %, depending on the system. The operating time of the genset is not limited. The typical area of application for this is gensets that supply systems continuously in stand-alone operation.

Limited-time running power Maximum power (LTP - Limited-Time Running Power) is the maximum power that a genset can deliver within 500 hours per year. The genset may be operated continuously for 300 hours.

Performance Data

Engine Brand & Model		Baudouin / 6M11G150/5
Alternator Brand & Model		Newpower / NW/N138
Frequency & Phase		50 Hz & 3 Phase
Engine Speed (RPM)		1500
Tank Capacity (L)		260
Fuel Consumption (L/h)	110% Load	33,1
	100% Load	30,2
	75% Load	23
	50% Load	15,9
Standard Noise Level @ 7m (Soundproof Sets)		ca. 70 dB

Dimensions and Weights

Content		Open Skid	Canopied
Dimensions (mm)	L	2350 mm	3320 mm
	B	1100 mm	1100 mm
	H	1400 mm	1800 mm
Weights (Kg)		1407 kg	1828 kg

The dimensions of the unit may vary depending on the equipment. Please inform us exactly about the area of application.

The Reliable Supplier for Power System Solution

Engine Features

Baudouin is a company founded in France in 1918 that manufactures diesel engines primarily for marine applications and generators. Baudouin's generator engines are known for their high performance, reliability and durability. These engines are available in various power ranges and are often used in industrial plants, ships, harbors, emergency power supplies and other applications. Thanks to their high efficiency, strong performance, long service life and environmentally friendly characteristics, Baudouin motors have become a popular choice in industrial and marine applications.

Typical Engine Data / Engine Brand & Model: Baudouin / 6M11G150/5

No. Of Cylinders / Alignment	6 / Inline	Displacement (L)	6,75
Bore / Stroke	105 mm / 130 mm		
Induction	Turbocharged and Aftercooled	Governing Type	Electronic
Cooling Method	Water	Net Weight (kg)	692
Lubricant Oil	15W-40	Exhaust Outlet Temperature 50 Hz	550
Emission Standard	Stage II	Exhaust Gas Flow 50 Hz	23,65
Oil Capacity (L)	17	Combustion Air Flow 50 Hz	8,76
Engine Gross Power (Standby 50 Hz)	140 kW	Cooling Air Flow 50 Hz	304,5
Compression Ratio	18:1	Coolant Capacity (L)	17

Alternator Data / Brand & Model: Newpower & NWN 138

Nominal Performance	125 kVA	Insulation class	H
Maximum Performance	138 kVA	Protection	IP23
Winding	%100 Copper	Winding pitch	2 / 3
Brush type	Brushless	Amortisseur winding	Full
Generator type	Synchronise	Ambient temp	50 ºC
Bearing	single	Stator rated temp	125 ºC
A.V.R.	SX440 / SX460	Phase Sequence	A(U), B(V), C(W)
Voltage Regulation	±1.0%	THF(BS EN60034-1)	<2%
Trigger system	Self Excitation	TIF(NEMA MG 1-22)	<50

Controlsystem:



InteliLite 4 AMF 8 is a single genset controller for standby and prime power applications. Intuitive, flexible, easy to install and use, the InteliLite 4 AMF 8 controller offers multiple configuration options to create the best solution for on-site and remote control and monitoring of your gensets.

The Reliable Supplier for Power System Solution

Characteristic

Included	Optional
o 4-stroke 1500 rpm, water-cooled heavy-duty diesel engine o Replaceable dry type air filter o Heat resistant cooler for 50°C. o Flexible oil lines and oil drain valve o Single layer, brushless AC generator o batteries and cables o Circuit breaker - RCD protection o Industrial silencer Soundproof Plus o battery charger o cooling water heater o sockets o Galvanized canopy o circuit diagram o User Manual and Instruction Manual	o Automatic transfer switch o External fuel tank o fuel heater o Oil heater o Fuel filling system (automatic / manual) o Analog displays

NEWPOWER

167/5000

We reserve the right to make changes to the model, specifications, color, configuration and accessories without prior notice.Please contact us before placing your order.